

RadarHub™

For EchoGuard® family of radars

Managed Surveillance. Intelligently.

Pre-engineered C2 solution for deployment, networking, and operations of multi-radar installations.

Easily integrate with security system infrastructure or quickly deploy standalone hemispherical surveillance for temporary missions.

Standardize every install and simplify support and maintenance.

Flexible support for a variety of sensor fusion configurations (radar + camera + add'l sensor, eg ADS-B, RF).

Weatherproof NEMA 3R lockable polycarbonate enclosure and reconfigurable DIN rails for customizing to need.

Fixed mast mount or ground station options.

UL-508A compliant design and construction.





RadarHub

For EchoGuard family of radars



Ordering Information

RadarHub Edge Compute 700-0021-201-100

RadarHub Basic 700-0021-202-100

Ground Stand Kit 700-0004-201-100

Cabinet

Sealing NEMA 3R w/ shrouded fan ports

Thermal management Thermostat controlled filtered dual

cooling fans + heater strip
Operating temperature -40 C to +49 C ambient

Storage temperature -40 C to +70 C ambient Dimensions 18" h x 16" w x 10" d

Mounting configuration Pole mount (dual band clamp)

Ground stand (optional)

Enclosure Lockable, light gray with gloss finish,

UV resistant polycarbonate

Design Industrial DIN-rail modules
Regulatory UL-508A compliant design and

construction

Warranty 1-year manufacturing

Sensors & Networking

Supported radars Up to 5 via IP67 cable glands

Add'l sensor support 1x 802.11bt 90W PoE++ PTZ camera
1x 802.11at 30W POE+ Aux sensor

Network switch 10-port Gigabit TCP/IP switch

Data I/O 3x RJ45 IP67 sealed ports (external PTZ

camera, Aux sensor)

Power

Power input 120/240V AC single phase

Max 500W (depending upon sensor

number and configuration)

Power protection Input surge, transient overvoltage and

15A circuit breaker

Power control Local and remote IP-controlled power

sequencing of radar sensors

Convenience outlet GFCI-protected 5A dual outlet for

computer and test equipment

Edge Compute (optional)

Echodyne software Rugged embedded

PC Environmental

computer

Pre-installed Acuity software suite AMD Ryzen quad-core V1605B CPU 4x Gigabit 802.3at PoE+ ports

Memory: 16 GB DDR4 2666 Storage: 2x 512 GB SSD O/S: Windows 10 Pro 64-bit

Ubuntu 18.04 LTS 64-bit (optional) Vibration: MIL-STD-810G, Method

514.6, Category 4

EMC: CE/FCC Class A, per EN 55032

& EN 55024